



Essentials Deactivation Controller

The compact Sensormatic Essentials Deactivation Controller offers fast, accurate checkout service to drive revenue and increase shopper throughput. This device powers Essentials deactivation antennas to effectively deactivate active AM EAS labels, regardless of orientation. Its small footprint allows vertical or horizontal installation to meet individual retailers' needs.

Retailer Values

- // Reliable deactivation, regardless of label orientation, for fewer nuisance alarms and a better customer experience
- // Compact design allows flexible installation options to fit virtually any retailer's needs

Product Code

ZBAMB1200C

Product Compatibility

Essentials Deactivators
Remote Alarm Module

Specifications

Length	29.4cm (11.6in)
Width	18.7cm (7.4in)
Height	8.15cm (3.2in)
Weight	1.43kg (3.15lbs)
Power Cord Length	Approx. 1.8–2.5m (6–8.2ft)

Electrical

Voltage Input

100–240Vac (±10%)
50/60Hz (±5%)

AC Line Current

1.5Arms max.

Environmental Constraints

Operating Temperature

0°C to 40°C (32°F to 104°F)

Non-Operating Temperature

–40°C to 70°C (–40°F to 158°F)

Relative Humidity

0 to 90%, non-condensing

Declarations

EMC

47 CFR, Part 15
RSS 210
EN 300 330
EN 301 489

Safety (second edition)

UL 60950-1
CSA-C22.2.60950-1
EN 60950-1

Environmental Rating

IP20

CE This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.