



SlimPad Deactivator

The Sensormatic SlimPad Deactivator offers reliable deactivation for checkstands with limited space. The SlimPad automatically deactivates active AM EAS labels up to 15cm (6in) above its surface at a throughput speed of up to 200cm/sec (80in/sec). Its narrow design allows installation on either side of the scanner to help maintain the proper flow of products: first over the scanner, then over the deactivator. The optional Remote Alarm Module can be mounted almost anywhere on the checkstand. The alarm module provides audible and visual confirmations when active labels are detected and deactivated. The locking key feature within the alarm module prevents unauthorized use of the SlimPad when point-of-sale is unattended.

When connected to a compatible EAS data management device, real-time deactivation counts can be generated into user-friendly customizable reports to provide business-critical data.

Retailer Values

- // Narrow design allows installation on either side of the scanner to maintain proper "scan-deactivation" product flow

- // Fast deactivation accelerates check-out and alleviates unnecessary shopper delays

- // EAS connectivity option allows generation of operational information to help quickly identify and correct performance issues

- // Built-in audible and visual indicators provide immediate feedback when active labels are detected and deactivated, enhancing front-end productivity

Product Codes

ZBSMP-SL

SlimPad Deactivator, AMB9010-IPS Controller, Remote Alarm Module, Power Cord

ZESMPRO

Controller with Cord

ZBAMB9010-IPS

AMB9010-IPS Controller Only

ZBSMPSP

SlimPad Deactivator Only

ZPSTP-RA

Remote Alarm Module

ZPSL-B2

Under-the-Counter Mounting Bracket

ZPSL-B3

End-of-the-Counter Cantilever Bracket

Product Compatibility

All Sensormatic AM EAS Labels
Local Device Manager II (LDM II)
Remote Alarm Module

Specifications

Length..... 35.7cm (14.0in)

Width 11.4cm (4.5in)

Height 7.0cm (2.8in)

Weight 6.5kg (14.3lbs)

Pad Cable Length..... 3m (10ft)

Electrical

Requires Universal Controller (ZBAMB9010-IPS)

Environmental Constraints

Operating Frequency

58 kHz

Operating Temperature

0°C to 40°C (32°F to 104°F)

CE This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.