



Ultra•Strip III Insertable Label

The Ultra•Strip III Insertable Label is designed to be inserted into plastic shrink wrapped packaging such as CD cases and perfume boxes. It should not be inserted into products intended for children's use. The bag format is intended for hand application.

Retailer Values

- // Ideal for CDs, perfume products or other plastic shrink wrapped boxes
- // Utilizes proven Sensormatic AM technology and manufacturing process to provide the highest in detection performance
- // Reactivable for unlimited reuse
- // Works well on liquids, foils and in metal shopping carts
- // Robust construction provides optimal merchandise protection

Product Codes

ZLDRCI5K2

Technology

AM

Environmental Constraints

Temperature

Maximum storage temperature for up to 96 hours=65°C (150°F).

Humidity

Unaffected by 80% humidity at 65°C (150°F), up to 96 hours.

Shelf Life

Two years from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 50-70% RH.

Product Compatibility

Sensormatic AM detection and deactivation devices.

Mode of Application

Hand

Materials of Construction

Plastic Substrait

Polystyrene—Maximum thickness 0.51 mm (0.02in)

Plastic Substrate

Polystyrene/Polyethylene 0.3mm (0.015in) thickness

Magnetic Acoustic Resonator

Proprietary resonant magnetic material. Amorphous alloy based on iron, and containing nickel, cobalt, boron and silicon

Laminate

Low Density Polyethylene/Polyester/ Polyethylene-0.127mm (0.0050in)

Bias

Proprietary semi-hard magnetic material containing iron, nickel and chromium

Adhesive

Double-coated, rubber-based adhesive:

- // 2.4mil thick per side
- // Minimum peel strength of 2.27kg/5lbs

Dimensions

Color	Barcode
Length	50mm ± 1mm (1.968in ± 0.039in)
Width	9.25mm ± 0.5mm (0.364in ± 0.020in)

Label Thickness

(excluding liner)...2.1mm (0.082in) typical

Labels Per Bag1,000

Note: Warranty terms and conditions are as specified in the applicable Sales Agreement.

CE The acousto-magnetic (AM) label is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

See Sensormatic.com for Usage Instructions

Additional Consideration:

- // Product is for the European market only. Not for use in the USA
- // Placement of labels is to be in accordance with the Product Usage Guidelines located in each box
- // Due to usage, contact deactivation is not recommended

SHEET SPECS	
	Sheet
PRODUCT CODE	ZLDRCI5K2
Case Weight	3.56kg (7.85lbs)
External Carton Dimensions	300 x 250 x 200mm (11.81 x 9.84 x 7.84in)
External Cubic Ft. Per Case	0.53
Order multiple	5,000-unit case (5 bags of 1,000 labels per case)