





# APX Non-Deactivatable Sheet Label (NDL)

The APX Non-Deactivatable Label delivers the stability and resistance to deactivation similar to a Sensormatic hard tag. This reusable anti-shoplifting label provides the highest anti-theft protection option for safers and asset protection solutions. The label remains active in a typical point-ofsale environment where it may come in close proximity to deactivators and magnetic detachers.

# **Retailer Values**

- // Non-deactivatable format designed to protect safers and other asset protection solutions
- // Utilizes the proven Sensormatic AM technology to provide the highest detection performance available
- // Works well on liquids, foils and in metal shopping carts
- // Robust construction provides optimal merchandise protection

#### **Product Codes**

ZLAPX-NDL

#### **Technology**

AM

### **Environmental Constraints**

#### Temperature

Maximum storage temperature not to exceed 50°C (122°F) for 96 hours at 80% RH.

#### Humidity

Unaffected by 80% humidity at 50°C (122°F), up to 96 hours.

#### Shelf Life

Two years from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 30-80% RH.

#### **Product Compatibility**

Sensormatic AM detection and deactivation devices.

# Mode of Application Hand

# **Dimensions**

Color	Red
Length	. 45.21mm ± 0.5mm (1.786in ± 0.020in)
Width	10.67mm ± 0.5mm (0.420in ± 0.020in)
Label Thickness	
(excluding liner)	Maximum
	2.1mm (0.082in)
(including liner)	Maximum
	2.3mm (0.090in)
Labels Per Sheet	

**Note:** Warranty terms and conditions are as specified in the applicable Sales Agreement.

CE The acousto-magnetic (AM) label is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

#### See <u>Sensormatic.com</u> for Usage Instructions

SHEET SPECS	
	Sheet
PRODUCT CODE	ZLAPX-NDL
Case Weight	2.85kg (6.28bs)
External Carton Dimensions	27.9 x 20 x 11cm (11 x 8 x 4.5in)
Cases Per Pallet	160
Order Multiple	4000-unit case

