

4IN1 Camera

1080P Tube Camera HS-4IN1-T031AA



- Board lens: 3.6mm
- Support CoC (UTC) to operate OSD MENU
- 2DNR/3DNR

Advantage

1. High video quality on HD 1080P.
2. HD video transmission without video quality loss & delay.
3. Long transmission distance.
4. The same connection structure as original analogue system without cable (Coax / UTP) changing.

Specifications

Model	HS-4IN1-T031AA
Pick up device	1/2.9" CMOS : 2.0 Mega
Solution	2441H + SONY 323
Resolution	1920(H) x 1080(V)
Video Output	AHD / CVBS / TVI / CVI
Min. Illumination	0.01 lux
IR Distance	25M
Lens	Board Lens: 3.6 mm
Electronic Shutter	Auto 1/60 (1/50) ~ 1/50,000 sec / FLK
S/N Ratio	More than 60 dB(AGC OFF)
2DNR	Yes
3DNR	Yes
Control	CoC (Control Over Coaxial)
Power Source	DC12V ± 10% / 1A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 70°C (-4 °F ~ 158 °F)
Dimension	132.7mm x ø85 (Diameter)mm
Weatherproof	IP66

Dimension Unit : mm

