

## 2M IP Camera HS-D043QR



### Software

- 2MP (1920 × 1080)
- 3D DNR / DWDR
- ROI coding
- Support smart phone, iPad, remote monitoring
- Support P2P

### Hardware Specification

- 1/2.8" CMOS.
- Built-in IR Cut Removable.
- Built-in PoE.
- Class IP66 Weatherproof.

## Specifications

Model	HS-D043QR
Compression method	H.264 / M-JPEG
Image Sensor	1/2.8" CMOS
Image Pixels	1920 x 1080
Resolution	1080P (1920x1080) / 720P (1280x720) / D1 / CIF / 480x240
Triple streaming	S1: 1920x1080@30fps S2: 1280x720@10fps / D1@30fps / CIF@30fps S3: CIF@30fps / 480x240@30fps
Bit Rate	64Kbps ~ 8Mbps
Stream transmission	CBR / VBR
LAN Port	Ethernet (10/100Base-T), RJ45 connector
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Web Browser	Microsoft Internet Explorer 8.0 or above
Electronic Shutter	Auto 1/25 ~ 1/100,000 sec.
Min. Illumination	0 Lux (IR LED ON)
IR Distance	20M
ICR	Yes
PoE	Yes
Lens Type	Board Lens 3.6mm
Power Source	DC12V
Operating Temperature	-10°C~50°C, 10%~90% humidity
Weatherproof	IP66
Dimension	87 × Φ108 mm

## Dimension Unit : mm

