

H.265 NVR Plug & Play

H.265/H.264 Setup Free PoE NVR HS-PB4311/HS-PB8311



- Independent 4/8 port PoE supported.
- Plug & Play supported.
- Multi stream supported.
- Mobile remote surveillance. (iPhone/ iPad/ Android)
- 2 way audio. (conference)
- Recording retention function supported.
- USB or remote firmware upgrade supported.
- Network online user management.
- Recorded file protection supported.
- Intensive security function by authority.
- Directly AVI format backup.
- Firefox and IE browser supported. (Windows)
- Safari browser supported on MAC OS.
- ONVIF V2.4(Profile S).
- Digital zoom on live and playback.

Specifications

Model	HS-PB4311	HS-PB8311
Operation System	Embedded Linux	
Compression Method	H.265/H.264	
Video	VGA	1 (1920 x 1080 / 1280 x 1024)
	HDMI	1 (4K : 3840 x 2160 / 1920 x 1080 / 1280 x 1024)
Color	16.7 million	
Display Channel	1 / 4	1 / 4 / 9
Simultaneously Playback Channel	4	8
Record Bitrate	1 M ~ 8 M bps	
Recording Resolution (Total)	5M / 4M / 3M / 1080P / 720P @120fps	
Record Quality	Highest / Higher / Medium / Lower / Lowest	
Recording Mode	Auto / manual / schedule	
Playback Mode	Date & Time search / Event search	
Multi-task	Live / Record / Play / Network / Backup	
Backup	USB 2.0 / Network remote backup	
Storage	SATA x 1 (8TB)	
Audio Input/Output	RCA x1 ; RCA x1	
HDD Record Mode	Full stop / Overwrite	
Load Bandwidth (Mbps)	40	64
Ethernet	RJ45 x 1 (10/100 M Base-T)	
POE Build-In	RJ45 x 4	RJ45 x 8
Mobile Surveillance	iPhone / iPad / Android	
Mouse	Standard	
Network-Function	Support licensed CMS(100CH) / EMAP/ IE	
Network Connection	TCP/IP, PPPoE, DHCP, DDNS	
Client Application	Display / Playback / Backup / DVR control / PTZ Control	
Power Supply	DC12V	
Operating Temperature	5°C ~ 40°C	
Operating Humidity	10 ~ 90 %	
Dimension	300(W) x 45(H) x 248.4(D) mm	

Dimension Unit : mm

