

4MP IP Camera (With motorized lens)

HS-T036QC



Software

- 4MP (2560 x 1440)
- 3D DNR / DWDR
- Support smart phone, iPad, remote monitoring
- Support P2P
- ROI
- 2 way audio

Hardware Specification

- 1/3" CMOS.
- Built-in IR Cut Removable.
- Aluminum Alloy Housing for Better Heat Dissipation.
- Built-in PoE.
- Class IP66 Weatherproof.
- 60M IR distance.

Specifications

Model	HS-T036QC
Compression Method	H.265 / H.264 / M-JPEG
Image Sensor	1/3" CMOS
Image Pixels	2560 x 1440
Resolution	4MP(2560x1440) / 1080P (1920x1080) / 720P (1280x720) / D1 / CIF
Triple streaming	S1: 4MP@30fps / 1920x1080@30fps S2: D1@30fps / CIF@30fps S3: D1@30fps / CIF@30fps
Bit Rate	64Kbps ~ 8Mbps
Stream transmission	CBR / VBR
Lens	Motorized zoom 2.8~12mm
Min. Illumination	0 Lux (IR LED ON)
Electronic Shutter	1/25 ~ 1/100,000 sec.
Storage	Network remote storage / Support TF card, the max capacity is 128 GB (class10 or above)
Alarm Input/Output	1/1
Audio Input/Output	1/1
IR Distance	60 M
LAN Port	Ethernet (10/100Base-T), RJ45 connector
ICR	Yes
PoE	Yes
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Web Browser	Microsoft Internet Explorer 8.0 or above
Power Source	DC12V
Operating Temperature	-10°C~50°C, 10%~90% humidity
Dimension	283.9 x ø108.9 (Diameter)mm
Weatherproof	IP66

Dimension Unit : mm

