

3M IP Camera

HS-T038QM



Software

- 3MP (2048 × 1536)
- 3D DNR / DWDR
- ROI coding
- Support smart phone, iPad, remote monitoring
- Support P2P

Hardware Specification

- 1/3" CMOS.
- Built-in IR Cut Removable.
- Aluminum Alloy Housing for Better Heat Dissipation.
- Built-in PoE.
- Class IP66 Weatherproof.
- 15M IR distance.

Specifications

Model	HS-T038QM
Compression method	H.264 / M-JPEG
Image Sensor	1/3" CMOS
Image Pixels	2048 x 1536
Resolution	3MP (2048x1536) / 1080P (1920x1080) / 720P (1280x720) / D1 / CIF / 480x240
Triple streaming	S1: 3MP@30fps / 1920x1080@30fps S2: 1280x720@10fps / D1@30fps / CIF@30fps S3: CIF@30fps / 480x240@30fps
Bit Rate	64Kbps ~ 8Mbps
Stream transmission	CBR / VBR
LAN Port	Ethernet (10/100Base-T), RJ45 connector
Protocol	TCP/IP , UDP , DHCP , NTP , RTSP , PPPoE , DDNS , SMTP , FTP
Web Browser	Microsoft Internet Explorer 8.0 or above
Electronic Shutter	Auto 1/25 ~ 1/100,000 sec.
Min. Illumination	0.01 Lux (IR LED ON)
IR Distance	15M
ICR	Yes
PoE	Yes
Lens Type	Board Lens 3.6mm
Audio Out	DC12V / PoE
Operating Temperature	-20°C~50°C,10% ~90% humidity
Dimension	Φ64 ×183 mm
Weatherproof	IP66

Dimension Unit : mm

