

3M IP Camera HS-T039QY/HS-T037QL



Software

- 3MP (2048 × 1536)
- 3D DNR / DWDR
- ROI coding
- Support smart phone, iPad, remote monitoring
- Support P2P

Hardware Specification

- 1/3" CMOS.
- Built-in IR Cut Removable.
- Aluminum Alloy Housing for Better Heat Dissipation.
- Built-in PoE.
- Class IP66 Weatherproof.
- 30~40m IR distance.

Specifications

Model	HS-T039QY	HS-T037QL
Compression method	H.264 / M-JPEG	
Image Sensor	1/3" CMOS	
Image Pixels	2048 x 1536	
Resolution	3MP (2048x1536) / 1080P (1920x1080) / 720P (1280x720) / D1 / CIF / 480x240	
Triple streaming	S1: 3MP@15fps / 1920x1080@30fps S2: 1280x720@10fps / D1@30fps / CIF@30fps S3: CIF@30fps / 480x240@30fps	
Bit Rate	64Kbps ~ 8Mbps	
Stream transmission	CBR / VBR	
LAN Port	Ethernet (10/100Base-T), RJ45 connector	
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP	
Web Browser	Microsoft Internet Explorer 8.0 or above	
Electronic Shutter	Auto 1/25 ~ 1/100,000 sec.	
Min. Illumination	0 Lux (IR LED ON)	
IR Distance	30 M	40 M
ICR	Yes	
PoE	Yes	
Lens Type	Board Lens 3.6mm	Vari-focal Lens 2.8~12mm
Power Source	DC12V / PoE	
Operating Temperature	-20°C~50°C, 10% ~90% humidity	
Dimension	219.4 x ø69(Diameter)mm	219.4 x ø86.7(Diameter)mm
Weatherproof	IP66	

Dimension Unit : mm

